

Single-phase spotlight - Slim, 5 W, DIM, 2,700 K, black



Image similar

Prices

List price (VAT included)	79.95 EUR per 1
Minimum order quantity	1
Order step	1

Information

Order number	707202
EAN	4042943179371

Description

- glare-free thanks to low UGR value (19)
- slim design with just 39 mm diameter
- incl. silver-coloured reflector ring

Features

RRP incl. VAT	79.95 EUR
Housing Material	Aluminium
Housing Color	Black
Housing Color, Color System	Deep black RAL 9005
Frequency	50 / 60 Hz
Light Source	Light source changeable TC
Light Source	LED
Number of Light Sources	1
Luminous Efficiency	100.0 lm/W
Light Distribution	Symmetric
Colour Consistency	6 SDCM
Switching Cycles	100000
Rotation Angle	330 Degree
Swivel Angle	60 Degree
Product weight	222 g
Connection Type	Adapter
Power Supply Unit incl.	Yes
Power Consumption	5 kWh/1000h
Power Factor	0.8
Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 65 °C
Mounting Type	Top mounting
Mounting Location	Inside
Mounting Area	Ceiling installation
Rated Input Voltage	220-240 V/AC
Rated Input	5.0 W

Control	Trailing-edge dimmer
Control	Leading-edge dimmer
Dimmable	Yes
Motion Detector	No
Power Supply Unit Changeable	Yes by technician
Protection Class	Protection class I /protective grounding
UGR	19
Lightcolor	Warm white (WW)
Color Temperature	2700 K
Colour Rendering Index (Ra)	90
Rated Luminous Flux	500 lm
Light direction	Below
Rated Angle of Reflection	36 Degree
Turning and Swiveling Range	Rotatable
Length	197 mm
Diameter	39 mm
IP Protection Class	IP 20
Life Time L70 / B50	50000 h

