

## APPLICATION

- LED protection and light diffusion in lighting fixtures


## MOUNTING

- to the profile, by pressing

## ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance  $\pm 1.5$  mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)  
 - when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

## TECHNICAL DRAWING




## TECHNICAL SPECIFICATIONS


Material	PC
Shape	flat
Maximum length on request	3000 mm
Width	46.5 mm
Possibility of obtaining a line of light	yes
UV resistance	yes

Finish	Light transmission	Length	Ref
frosted	68 %	1000 mm	B17052M_1
		2005 mm	B17052M_2
		3010 mm	B17052M_3
clear	94 %	1000 mm	B17052T_1
		2005 mm	B17052T_2
		3010 mm	B17052T_3
frosted	70 %	1000 mm	B17058F_1

## RELATED PROFILES > FOR MAIN LIGHTING



**DES**  
A18030



**GLADES**  
A18036


# Cover DHS

Ref. B17052M, B17052T

## RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



**KIDES**  
A18031



**OBIT**  
A04826