

Cover HS-22

Ref. B17011F, B17011C, B17011M



- Recommended for the construction of sealed lighting fixtures

APPLICATION

- LED protection and light diffusion in lighting fixtures


MOUNTING

- to the profile, by pressing

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	PC					
Shape	flat					
Possibility of bending	yes					
UV resistance	yes					
Finish	Maximum length on request	Light transmission	Length	Width	Possibility of obtaining a line of light	Ref
frosted	3000 mm	65 %	1000 mm	21 mm	yes	B17011F_1
			2005 mm			B17011F_2
			3010 mm			B17011F_3
clear	3000 mm	88 %	1000 mm	21 mm	no	B17011C_1
			2005 mm			B17011C_2
			3010 mm			B17011C_3
microprism	3050 mm	90.5 %	1000 mm	23.6 mm	no	B17011M_1
			3050 mm			B17011M_3

Cover HS-22

Ref. B17011F, B17011C, B17011M

RELATED PROFILES




LESTO
B5551

RELATED PROFILES > ARCHITECTURAL




DIPOK-US
A01233



DIPOKET
A01177



GIZA
A05556



GIZA-DUO-LL
A02162



GIZA-LL
A00758



GIZA-LL-T
A02479



GIZA-LL-UST
A02724N



GLAZA-DUO
A03059



KOZEL
A06454



KOZUS
A07823



KOZUS-CR
A00600



LARKO
A05552



LIPOD
A05554



LOC-30
A18015



LOKOM
A05553




OPAC-30
A06164

Cover HS-22


Ref. B17011F, B17011C, B17011M

RELATED PROFILES > FACADE



FASKO
A04323

RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



KIDES-DUO
A18032



WERKIN
A18025

RELATED PROFILES > STAIRS ILLUMINATION



STEPUS
A18038